

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
22 April 2004 (22.04.2004)

PCT

(10) International Publication Number
WO 2004/034756 A2

(51) International Patent Classification⁷: H05K 1/00 (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CI, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(21) International Application Number: PCT/DK2003/000630

(22) International Filing Date: 25 September 2003 (25.09.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data: PA 2002 01512 8 October 2002 (08.10.2002) DK

(71) Applicant (*for all designated States except US*): OTICON A/S [DK/DK]; Strandvejen 58, DK-2900 Hellerup (DK).


(72) Inventors; and

(75) Inventors/Applicants (*for US only*): MEHR, Ulrik [DK/DK]; C/O Oticon A/S, Strandvejen 58, DK-2900 Hellerup (DK). JOHANSEN, Jesper, B. [DK/DK]; C/O Oticon A/S, Strandvejen 58, DK-2900 Hellerup (DK).

(74) Agent: POULSEN, Henning, Knak; Oticon A/S, Strandvejen 58, DK-2900 Hellerup (DK).

Published:
— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.



WO 2004/034756 A2

(54) Title: LAYERED STRUCTURE WITH ELECTRIC LEADS FOR A BODY WORN DEVICE

(57) Abstract: Layered structure for a head worn device, wherein electric signals are fed along metallic leads, which are adhered to a layer on or within the layered structure and where a first and a second lead for connecting a first and a second terminal of a component are provided and whereby the two leads are passed side by side and alternating on the two sides of the layer, and in such a manner that the first and second lead will cross one another at an angle but passing on each their side of the print layer.